ATEN Technology, Inc.
www.aten-usa.com

MasterView KVM - Model CS9138 CS9138

Your business is growing faster than you expected and four computers simply aren't enough to meet your needs. Not a problem! ATEN's new eight-port MasterView Plus is just the tool you need to help reduce the need for redundant hardware. Eight monitors, mice and keyboards are simply too expensive, bulky and down-right inconvenient for most system administrators. Why bother when you can control all eight, or even up to 512 computers with a single keyboard, monitor and mouse. Just think of the time, space and money you'll save. But our MasterView Plus is much more than a simple eight-port KVM switch. Built-in AutoScan mode lets you conveniently monitor every attached computer for a specified amount of time, while our On Screen Display technology allows you to assign a unique name to each computer and access it via a slick, menu-driven interface. With it's 1U, 19?rack-mountable casing and status-monitoring LEDs, the MasterView Plus is the perfect switch for your server room or any other multi-computer environment.

Distributor Part NO. : Contact Aten for part number @ 949.428.1111

Features:

- Cascadable To Three Levels - Control Up to 512 PCs From a Single Console
- No Software Required - PC Selection via Front Panel Switches, Hot Keys, or OSD (On Screen Display)
- Quick View Scan Feature for Monitoring Selected PCs
- PS/2 and Serial Mouse Emulation Provided For System Bootup
- Console's PS/2 Mouse Controls All Connected PCs - Even Those With Serial Mice
- Microsoft Intellimouse Pro, Logitech FirstMouse, MouseMan, IBM Scrollpoint Mouse
- Support SVGA, VGA and Multisync Monitor Support Superior Video Quality; 1920x1440; DDC2B LED Display For Easy Status Monitoring
- Rack Mountable in 19" System Rack
- Hot Pluggable - Add or Remove PCs for Maintenance Without Powering Down the Switch

Requirements:

- 1 VGA, SVGA, or Multisync monitor capable of the highest resolution that you will be using on any PC in the installation
- 1 PS/2 Style Mouse
- 1 PS/2 Style Keyboard
- 1 VGA, SVGA or Multisync card
- 1 6-pin mini-DIN (PS/2 Style), or DB-9 (standard serial), mouse port

- 1 6-pin mini-DIN (PS/2 Style) keyboard port with +5V DC on pin 4 and Ground on pin 3, or 1 5-pin mini-DIN (AT Style) keyboard port with + 5 DC on pin 5 and Ground on pin 4

Package Content:

- 1 x CS9138 KVM Switch
- 1 x Power Adapter
- 2 x Rack Mounting Brackets with Screws
- 1 x User Manual

Specification :

Housing	
Case	Metal
CPU Connectors	
Mouse	8x6 pin mini-DIN Female (PS/2)
Keyboard	8x6 pin mini-DIN Female (PS/2)
Monitor	8xHDDB15 Male
Console Connectors	
Mouse	1x6 pin mini-DIN Female (PS/2)
Keyboard	1x6 pin mini-DIN Female (PS/2)
Monitor	1xHDDB15 Female
Power	
Voltage	DC + 9V
Amps	400 mA(Max.)
LEDs	
Power On	1
Selected	8
On Line	8
Port Selection	Push Buttons, Hot Keys, or OSD
Power Consumption	DC 9V, 1.08W
Video Resolution	1920x1440; DDC2B
Scan Interval	3, 5, 10, 15, 20, 30, 40, 60 seconds
Emulation	
Keyboard	PS/2, AT
Mouse	PS/2, Serial
Computer Connections	
Direct	8
Daisy Chain or Cascading	512
Operating Temperature	32F~122F (0C~50C)
Storage Temperature	-4F~140F (-20C~60C)
Security	1-level password security
Power Adaptor Part #	

for North America	# 0AD1-0909-031G
for Continental Europe	# 0AD6-1909-031G
for UK	# 0AD4-3909-031G
Unit Dimensions	
Width	17.0 in. (43.2 cm)
Height	1.8 in. (4.4 cm)
Depth	6.0 in. (15.2 cm)
Unit Package Dimensions	
Width	21.0 in. (54.6 cm)
Height	4.3 in. (10.8 cm)
Depth	9.0 in. (22.9 cm)
Master Carton	
Width	15.5 in. (39.4 cm)
Height	10.3 in. (26.0 cm)
Depth	22.0 in. (55.9 cm)
Master Carton Qty.	3
Weight	
Master Carton Wt.	26.0 lb. (11.7 kg)
Unit Pack Wt.	8.0 lb. (3.6 kg)
Unit Wt.	6.2 lb. (2.8 kg)